




Dimension: (Unit: mm)



Common Rating

Step angle	1.8°
Position accuracy	1.8±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100MOhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max.0.02mm(Load 450g)
Axial play	Max.0.08mm(Load 900g)


技术要求:

- 1、未注形位公差按GB/T 1184-K;
 - 2、未注尺寸公差按GB/T 1804-m。
- (除非另外指定)


Specification:

Current/phase	1.2 A
Voltage	2.64 V
DC Resistance/phase ±10%	2.2 Ω
Inductance/phase ±20%	2.3 mH
Holding torque	0.13 N•m
Inertia	0.018 kg•cm ²
Weight	0.25 kg
Encoder resolution	1000 cpr

4-M2.5x0.45
DEEP 4.0MIN




Motor Connetions:



Encoder Signals

PIN	1	2	3	7	8	11	12	13
颜色	黑	红	白	橙	灰	黄	绿	蓝
定义	A+	VCC	GND	Z+	Z-	B+	B-	A-



设计 Designed		标准化 Standardized		材料(Material):	名称(Title)	混合伺服电机
制图 Drawn					型号(Model)	28HSM006-E1 MS30
校对 Proofread		审核 Checked		重量(Weight)/g:	图号(DWG No.)	LS-28HSM006-E1 MS30
工艺 Processed		批准 Approved		阶段标记(Stage Mark)	料号(Part No.)	
表单编号 Form No.	LS-QP-46-09A	版本/版次 Edition/Serial NO.	A/01	共1页第1页 Page 1 of 1	比例(Scale)	1:1

